



RESNET Conference February 29, 2016

> Theresa A. Weston, PhD DuPont Protective Solutions



Learning Objectives

□ Understand how building codes effect innovation

- Review the code compliance and alternate materials and methods criteria
- Understand the role of evaluation agencies and evaluation reports
- Review examples of compliance through alternate methods



Development



Model code language and requirements are written.



Adoption

Codes become law by being adopted by state or local agencies



Implementation



Codes are enforced by local code officials

- Code Interpretation
- Alternate means of compliance







Topics covered

QUPOND,

Material Substitution



M.F. Ashby, Materials Selection in Mechanical Design, 1992



Material Substitution





Codes Identified as Barriers to Innovation

"Code officials at the local level have the legal authority to accept or reject the application of any new building product or system innovation. They can be the ultimate showstopper."

-- "*Overcoming Barriers to Innovation in the Home Building Industry*", Report for US HUD PD& R PATH, April 2005)

from Oster and Quigley, "Regulatory Barriers to the Diffusion of Innovation: Some Evidence from Building Codes", The Bell Journal of Economics, Vol. 8, No. 2 (Autumn, 1977), pp 361-377.



The National Commission on Urban Problems (1968) found that unnecessary housing costs are inherent in building codes that

- delay construction,
- prevent the use of modern materials,
- mandate antiquated and outdated provisions,
- inhibit mass production,
- prevent large-scale conventional construction, and
- are questionably administered.

Many communities, even those nominally adhering to model codes, prohibited costsaving materials and technologies that, generally, were allowed by the model codes. These communities added prohibitions of their own, or did not adopt the latest version of the model codes, etc.

FIGURE 1

DIFFUSION OF FOUR INNOVATIONS IN HOUSEBUILDING OVER TIME



Figure from Oster and Quigley, "Regulatory Barriers to the Diffusion of Innovation: Some Evidence from Building Codes", The Bell Journal of Economics, Vol. 8, No. 2 (Autumn, 1977), pp 361-377. Additional data for Listokin and Hattis



- "Building codes—and additional national, regional, or municipal regulations affecting the physical production of houses—prohibit innovation either by explicitly specifying only certain materials and methods, not providing speedy and impartial acceptance in the code where that explicit prohibition does not exist, or by being unfairly interpreted during permitting and inspections -
 - Martín, PATH Program Review & Strategy, Performance Metrics & Operating Plan, US
 Department of Housing and Urban Development PATH Draft





Data from Koebel, et. a., *The Diffusion of Innovation in the Residential Building Industry*, **Report** prepared for the U.S. Department of Housing and Urban Development Office of Policy Development and Research, January 2004



Product Development Process





Code and standard planning critical to innovation deployment

- "For an innovation to be accepted by the regulatory system, at a minimum it must be tested, certified, and evaluated. Once an evaluation report is prepared, these early steps may seem easy relative to educating code officials throughout the country about the product. Similarly, changing the model code (and ultimately state and local codes) so that it explicitly allows an innovation can be an even more difficult task. Although each of these steps can be expensive individually, they become more so the longer they are put off because of lack of understanding or bad planning."
 - Hassel et. al., "Building Better Homes, Prepared for the U.S. Department of Housing and Urban Development (HUD) Office of Policy Development and Research and the Partnership for Advancing Technology in Housing (PATH), 2003



Strategies Used to Gain Approval of Green Product, Material, System, or Design Application

		Sample				
~	Code	Code Official		e User		
Strategy	N	Percent	Ν	Percent		
Providing adequate supporting information	43	76.8	126	64.0		
Starting the approval process early to allow time to work with the building department	33	55.4	108	54.8		
Involving the building department staff early in the design process	31	55.4	103	52.3		
Providing precedents of code approval of similar approach in other jurisdictions	19	33.9	68	34.5		
Providing contact information for building officials in other jurisdictions with experience in the green approach	18	32.1	60	30.5		
Using outside experts	16	28.6	60	30.5		
Persistence/patience	10	17.9	100	50.8		
Other	7	12.5	20	10.2		

From Eisenberg, et al., Breaking Down the Barriers: Challenges and Solutions to Code Approval of Green Building, Development Center for Appropriate Technology Report, 2002.





How are materials specified in the code?



Materials / Systems can comply with code three ways:

□ Compliance to a direct reference

- Compliance through a referenced standard
- Compliance as an approved alternate material



Example: Compliance to a Direct Reference

IBC 1405.5 Wood veneers. Wood veneers on exterior walls of buildings of Type I, II, III and IV construction shall be not less than 1 inch (25 mm) nominal thickness, 0.438-inch (11.1 mm) exterior hardboard siding or 0.375-inch (9.5 mm) exterior-type wood structural panels or particleboard and shall conform to the following:

- 1. The veneer shall not exceed 40 feet (12 190 mm) in height above grade. Where fire-retardanttreated wood is used, the height shall not exceed 60 feet (18 290 mm) in height above grade.
- 2. The veneer is attached to or furred from a noncombustible backing that is fire-resistance rated as required by other provisions of this code.
- 3. Where open or spaced wood veneers (without concealed spaces) are used, they shall not project more than 24 inches (610 mm) from the building wall.

Specific materials and thicknesses

Attachment and

usage criteria

QUPOND:

Example: Compliance to a direct reference

R703.2 Water-resistive barrier. One layer of No. 15 asphalt felt, free from holes and breaks, **Specific material** complying with ASTM D226 for Type 1 felt or other approved water-resistive barrier shall be applied over studs or sheathing of all exterior walls. Such felt or material shall be applied horizontally, with the upper layer lapped over the lower layer not less than 2 inches (51 **Specific installation** mm). Where joints occur, felt shall be lapped method not less than 6 inches (152 mm). The felt or other approved material shall be continuous to the top of walls and terminated at penetrations and building appendages in a manner to meet the requirements of the exterior wall envelope as described in Section R703.1.



Example: Compliance through a Referenced Standard

2506.2 Standards. Gypsum board and gypsum panel products shall conform to the appropriate standards listed in Table 2506.2 and Chapter 35 and, where required for fire protection, shall conform to the provisions of Chapter 7.

TABLE 2506.2

AND OVERIM PANEL PRODUCTS MATERIALS AND ACCESSORIES

MATERIAL	STANDARD		
Cold-formed steel studs and track, structural	AISI S200 and ASTM C 955, Section 8		
Cold-formed steel studs and track, nonstructural	AISI S220 and ASTM C 645, Section 10		
Elastomeric joint sealants	ASTM C 920		
Fiber-reinforced gypsum panels	ASTM C 1278		
Glass mat gypsum backing panel	ASTM C 1178		
Glass mat gypsum panel 5	ASTM C 1658		
Glass mat gypsum substrate	ASTM C 1177		
Joint reinforcing tape and compound	ASTM C 474; C 475		
Nails for gypsum boards	ASTM C 514, F 547, F 1667		
Steel screws	ASTM C 954; C 1002		
Standard specification for gypsum board	ASTM C 1396 Referenced standard		
Testing gypsum and gypsum products	ASTM C 22; C 472; C 473		
	provide detailed		
	requirements		







Reference Standards in the IECC-2015 (36 Residential, 84 Commercial)









Compliance as an Approved Alternate Material

IECC-2015 SECTION R102

ALTERNATIVE MATERIALS, DESIGN AND METHODS OF CONSTRUCTION AND EQUIPMENT

R102.1 General. The provisions of this code are not intended to prevent the installation of any material or to prohibit any design or method of construction not specifically prescribed by this code, provided that any such alternative has been approved. The code official shall be permitted to approve an alternative material, design or method of construction where the code official finds that the proposed design is satisfactory and complies with the intent of the provisions of this code, and that the material, method or work offered is, for the purpose intended, at least the equivalent of that prescribed in this code.



Codes not intended

to prevent innovation

Equivalent to code provisions





from Follette, "Developments in Performance-Based Building Codes and Standard", FOREST PRODUCTS JOURNAL Vol. 50, No. 7/8 JULY/AUGUST 2000



"Ideally, construction standards would be a codification of performance specifications for newly constructed dwellings. In practice, however, standards are typically stated in terms of input requirements. To judge the acceptability of an innovation, then, the local building official must first evaluate the results of performance tests conducted by a wide variety of other agencies...on particular materials and designs. Based upon these evaluations, specific standards or input requirements are proposed and promulgated. Thus it appears that the progressiveness of local building codes should be directly related to the professional attributes of the local officials: the amount and type of their professional contact, their backgrounds, and their education."

• Oster and Quigley, "Regulatory Barriers to the Diffusion of Innovation: Some Evidence from Building Codes", The Bell Journal of Economics, Vol. 8, No. 2 (Autumn, 1977), pp 361-377.



Development of ALTERNATIVE MATERIALS, DESIGN AND METHODS OF CONSTRUCTION AND EQUIPMENT in the IECC





IECC 2003

Section 103

Alternate Materials – Method of construction, design, or insulating systems

103.1 General. The provisions of this code are not intended to prevent the use of any material, method of construction, design or insulating system not specifically prescribed herein, provided that such construction, design or insulating system has been approved by the code official as meeting the intent of the code.

Compliance with specific provisions of this code shall be determined through the use of computer software, worksheets, compliance manuals and other similar materials when they have been approved by the code official as meeting the intent of this code.

IECC 2006

SECTION 103 ALTERNATE MATERIALS—METHOD OF CONSTRUCTION, DESIGN OR INSULATING SYSTEMS

103.1 General. This code is not intended to prevent the use of any material, method of construction, design or insulating system not specifically prescribed herein, provided that such construction, design or insulating system has been approved by the code official as meeting the intent of this code.



IECC 2012

SECTION 102 ALTERNATE MATERIALS—METHOD OF CONSTRUCTION, DESIGN OR INSULATING SYSTEMS

102.1 General. This code is not intended to prevent the use of any material, method of construction, design or insulating system not specifically prescribed herein, provided that such construction, design or insulating system has been approved by the code official as meeting the intent of this code.

IECC 2015

SECTION R102 ALTERNATIVE MATERIALS, DESIGN AND METHODS OF CONSTRUCTION AND EQUIPMENT

R102.1 General. The provisions of this code are not intended to prevent the installation of any material or to prohibit any design or method of construction not specifically prescribed by this code, provided that any such alternative has been approved. The code official shall be permitted to approve an alternative material, design or method of construction where the code official finds that the proposed design is satisfactory and complies with the intent of the provisions of this code, and that the material, method or work offered is, for the purpose intended, at least the equivalent of that prescribed in this code. .



IBC 2015 Alternate Materials Section

104.11 Alternative materials, design and methods of construction and equipment. The provisions of this code are not intended to prevent the installation of any material or to prohibit any design or method of construction not specifically prescribed by this code, provided that any such alternative has been approved. An alternative material, design or method of construction shall be approved where the building official finds that the proposed design is satisfactory and complies with the intent of the provisions of this code, and that **the material**, **method or work offered is, for the purpose intended**, **not less than the equivalent of that prescribed in this code in quality, strength, effectiveness, fire resistance**, durability and safety. Where the alternative material, design or method of construction is not approved, the building official shall respond in writing, stating the reasons why the alternative was not approved.



Reason	N	Percent
Insufficient supporting information to satisfy safety concerns	40	71.4
Insufficient knowledge or technical expertise with the product, material, system, or design	30	53.6
Clear conflict with the intent of the code	28	50.0
Insufficient time in the building department to conduct sufficient research to understand the product, material, system, or design	18	32.1
General unfamiliarity with the product, material, system, or design	15	26.8
Personal experience with failure of the product, material, system, or design	9	16.1
Other	7	12.5
Inability of building department to meet tight schedule of applicant	6	10.7
Knowledge of problem of the approach in other jurisdictions	6	10.7

Code Officials' Reasons for Denial of Green Product, Material, System, or Design Application

From Eisenberg, et al., Breaking Down the Barriers: Challenges and Solutions to Code Approval of Green Building, Development Center for Appropriate Technology Report, 2002.



Alternate Materials





Deemed to Comply

C402.4.1.2.1 Materials. Materials with an air permeability no greater than 0.004 cfm/ft2 ($0.02 \text{ L/s} \cdot \text{m2}$) under a pressure differential of 0.3 inches water gauge (w.g.) (75 Pa) when tested in accordance with ASTM E 2178 shall comply with this section. Materials in Items 1 through 15 shall be deemed to comply with this section provided joints are sealed and materials are installed as air barriers in accordance with the manufacturer's instructions.

- 1. Plywood with a thickness of not less than 3/8 inch (10 mm).
- 2. Oriented strand board having a thickness of not less than 3/8 inch (10 mm).
- 3. Extruded polystyrene insulation board having a thickness of not less than 1/2 Must be installed (12 mm).
- 4. Foil-back polyisocyanurate insulation board having a thickness of not less that as an air barrier inch (12 mm).
- 5. Closed cell spray foam a minimum density of 1.5 pcf (2.4 kg/m3) having a thickness of not less than 11/2 inches (36 mm).
- 6. Open cell spray foam with a density between 0.4 and 1.5 pcf (0.6 and 2.4 kg/m3) and having a thickness of not less than 4.5 inches (113 mm).
- 7. Exterior or interior gypsum board having a thickness of not less than 1/2 inch (12 mm).
- 8. Cement board having a thickness of not less than 1/2 inch (12 mm).
- 9. Built up roofing membrane.
- 10. Modified bituminous roof membrane.
- 11. Fully adhered single-ply roof membrane.
- 12. A Portland cement/sand parge, or gypsum plaster having a thickness of not less than 5/8 inch (16 mm).
- 13. Cast-in-place and precast concrete.
- 14. Fully grouted concrete block masonry.
- 15. Sheet steel or aluminum.



IBC 2015

104.11 Alternative materials, design and methods of construction and equipment. The provisions of this code are not intended to prevent the installation of any material or to prohibit any design or method of construction not specifically prescribed by this code, provided that any such alternative has been approved. An alternative material, design or method of construction shall be approved where the building official finds that the proposed design is satisfactory and complies with the intent of the provisions of this code, and that the material, method or work offered is, for the purpose intended, not less than the equivalent of that prescribed in this code in quality, strength, effectiveness, fire resistance, durability and safety. Where the alternative material, design or method of construction is not approved, the building official shall respond in writing, stating the reasons why the alternative was not approved.

104.11.1 Research reports. Supporting data, where necessary to assist in the approval of materials or assemblies not specifically provided for in this code, shall consist of valid research reports from approved sources.

104.11.2 Tests. Whenever there is insufficient evidence of compliance with the provisions of this code, or evidence that a material or method does not conform to the requirements of this code, or in order to substantiate claims for alternative materials or methods, the building official shall have the authority to require tests as evidence of compliance to be made at no expense to the jurisdiction. Test methods shall be as specified in this code or by other recognized test standards. In the absence of recognized and accepted test methods, the building official shall approve the testing procedures. Tests shall be performed by an approved agency. Reports of such tests shall be retained by the building official for the period required for retention of public records.



IAPMO RESEARCH AND TESTING, INC.

5001 E. Philadelphia Street, Ontario, CA 91761-2816 • (909) 472-4100 • Fax (909) 472-4244 •

A Division of Arch	itectural Testing - Certification Services	magazin	C
Code Comp	liance Research Report	CCRR-0203	2
Subject to Renewal: Di Visit <u>www.ati-es.com</u> fi	3/08/2016 or current status	Issued: 08/20/2015 Page 1 of 2	_
			K
	فالمتحدين وحصوا فيتع		
		March Mildel	C
1.0 Subject	S ILC EVALUATION	Most Wider	
Ply Gem	JENVIUL		r
Ply Gem 2.0 Research	JENNIGE		r
2.0 Research 2.1 <u>Building</u>	ICC-ES Report		r
Ply Gem 2.0 Researct 2.1 <u>Building</u> 2012 Ini	ICC-ES Report		r s
Ply Gem 2.0 Researct 2.1 <u>Building</u> 2012 Ini 2012 Ini	ICC-ES Report	www.icc-es.org	r s
Ply Gem 2.0 Researct 2.1 <u>Building</u> 2012 In 2012 In 2.2 <u>Properti</u>	ICC-ES Report	www.icc-es.org This repo	r S
Ply Gem 2.0 Researct 2.1 <u>Building</u> 2012 In 2012 In 2012 In 2021 In 2021 Properti Weathe	ICC-ES Report ICC-ES (800) 423-6587 (562) 699-0543	www.icc-es.org This repo	۲ S n 15 58
Ply Gem 2.0 Researct 2.1 <u>Building</u> 2012 In 2012 In 2.2 <u>Properti</u> Weathe Termite	ICC-ES Report ICC-ES (800) 423-6587 (562) 699-0543	www.icc-es.org This repo	ר S ת 18 50
Ply Gem 2.0 Researct 2.1 <u>Building</u> 2012 In 2012 In 2.2 <u>Properti</u> Weathe Termite Surface	DIVISION: 07 00 00	www.icc-es.org This repo —THERMAL AND MOISTURE PRO	S
Ply Gem 2.0 Researct 2.1 <u>Building</u> 2012 In 2012 In 2012 In 2.2 <u>Properti</u> Weathe Termite Surface Structur on trim	DIVISION: 07 00 00 SECTION: 07 25 00-WA	-THERMAL AND MOISTURE PRO	T S DTECT
Ply Gem 2.0 Researct 2.1 <u>Building</u> 2012 Ini 2012 Ini 2.2 <u>Properti</u> Weathe Termite Surface Structur on trim 3.0 Descripti	DIVISION: 07 00 00 SECTION: 07 25 00-WA	This report This report THERMAL AND MOISTURE PRO THERMAL AND MOISTURE PRO TER-RESISTIVE BARRIERS/WEATION: 07 27 00—AIR BARRIERS	C S DTECT HER E
Ply Gem 2.0 Researct 2.1 <u>Building</u> 2012 In 2012 In 2012 In 2.2 <u>Properti</u> Weathe Termite Surface Structur on trim 3.0 Descript 3.1 General products are sections Inte trim and deck	DIVISION: 07 00 00 SECTION: 07 25 00-WA	WWW.ICC-ES.OFE This repo -THERMAL AND MOISTURE PRO TER-RESISTIVE BARRIERS/WEAT ON: 07 27 00—AIR BARRIERS	S DTECT HER B
Ply Gem 2.0 Researct 2.1 <u>Building</u> 2012 Ini 2012 Ini 2012 Ini 2.2 <u>Properti</u> Weathe Termite Surface Structur on trim 3.0 Descripti 3.1 General products are sections Inte trim and deck 3.2 Material are manufact	DIVISION: 07 00 00 SECTION: 07 25 00-WA	This report THERMAL AND MOISTURE PRO THERMAL AND MOISTURE PRO TER-RESISTIVE BARRIERS/WEATI DN: 07 27 00—AIR BARRIERS REPORT HOLDER:	T S DTECT HER I

104.11.1 Research reports. Supporting data, where necessary to assist in the approval of materials or assemblies not specifically provided for in this code, shall consist of valid research reports from approved sources.









NGB5 Green Certified Product Report #NGB5GCP-00042

Products:

Manufacturer S

The product(s) shown on this report have been independently verified as eligible products for use in achieving points toward project certification under ICC-700 National Green Building Standard. Home Innovation Research Labs authorizes accredited verifiers to award points toward certification without additional documentation when the product(s) is used as noted below.

	2008 NATIONAL GREEN B	SUILDENG S	TANDARD
PRACTICE#	PRACTICE DESCRIPTION	POINTIAL POINTI AVAILABLE	ADDITIONAL CONDITIONS OF USE TO AWARD POINTS
2008 Moile 602 12	Flaching datails on plans & installed et ALL as applicable enterier feasition discussions and valleys databalancy interpetimes and wall & roof chicanay interpetimes data cap above windows interpetimes data cap above windows incer ast fached or participal by presidents.	٠	Paulaing details must be shown on plans and product installed per plans.
2008 3/0-H8 701 4 5 5(1)	Windows and doors' Coulding, probability, Staching tage, from realizat, or weatherstripping forms a morphete six barrier. Mandatury for partification.	Manistur	Product must be installed per menufactures's instructions and building place.

2012 NATIONAL GREEN BUILDING STANDARD				
PRACTICE#	PRACTICE DESCRIPTION	POTENTIAL POINTS AVAILABLE	ADDITIONAL CONDITIONS OF USE TO AWARD POINTS	
2012 3FGRB 802 3.9(2)	All window herd and jon't Eaching is self-adhered Eaching completing with AAMA 711-07.	1	Finalizing details must be shown on plana and product installed per plana.	
2012 MORS 701.4.5 1.(c)	The building services is durably realed to limit air inflitution at specings between window and door arreadilies and their respective jouhn and framing.	Man datury	Product must be installed per manufactures's instructions and building plans.	

400 Pitani Gorge's Bealmard | Styne Marltons, MD 20174 | P.201, 249-4001 | P.201, 420 0244 | Bandhauvation.com



ICC-ES Acceptance Criteria

"Acceptance criteria are developed by the ICC-ES technical staff in consultation with the report applicant and with input from interested parties."

"New criteria and revisions to criteria are approved by the Evaluation Committee (made up entirely of code officials) during open public hearings or—in selected instances—through an alternate process that involves the solicitation of public comment through this web site."

"A criteria qualifies for the alternative process only if, in the opinion of ICC-ES staff, it meets one or more of the following requirements:

- The subject is nonstructural, does not involve life-safety, and is already addressed in nationally recognized standards or generally accepted industry standards.
- The subject requires its own criteria, but precedent for the new document already exists in other criteria or in the code.
- Relatively minor (noncontroversial) revisions are being proposed to an existing criteria."

Source: www.icc-es.org



ICC-ES Evaluation Report Generation Process



Source: www.icc-es.org



Evaluations have been conducted across a wide range of product areas:

DIVISION 01 00 00 GENERAL REQUIREMENTS DIVISION 03 00 00 CONCRETE DIVISION 04 00 00 MASONRY **DIVISION 05 00 00** METALS **DIVISION 06 00 00** WOOD, PLASTICS AND **COMPOSITES DIVISION 07 00 00** THERMAL AND MOISTURE PROTECTION DIVISION 08 00 00 OPENINGS **DIVISION 09 00 00** FINISHES DIVISION 10 00 00 **SPECIALTIES DIVISION 11 00 00** EQUIPMENT DIVISION 13 00 00 SPECIAL CONSTRUCTION DIVISION 14 00 00 CONVEYING EQUIPMENT

DIVISION 21 00 00 FIRE SUPPRESSION DIVISION 22 00 00 PLUMBING DIVISION 23 00 00 HEATING, VENTILATING, AND AIR-CONDITIONING (HVAC) **DIVISION 25 00 00** INTEGRATED **AUTOMATION DIVISION 26 00 00** ELECTRICAL DIVISION 27 00 00 COMMUNICATIONS DIVISION 28 00 00 ELECTRONIC SAFETY AND SECURITY **DIVISION 31 00 00** FARTHWORK **DIVISION 32 00 00 EXTERIOR IMPROVEMENTS DIVISION 33 00 00** UTILITIES DIVISION 40 00 00 **PROCESS INTEGRATION**

DIVISION 07 00 00 THERMAL AND MOISTURE PROTECTION



07 11 00 - Dampproofing	07 42 13 - Metal Wall Panels
07 13 00 - Sheet Waterproofing	07 42 43 - Composite Wall Panels
07 14 00 - Fluid-Applied Waterproofing	07 44 00 - Faced Panels
07 18 13 - Pedestrian Traffic Coatings	07 44 16 - Porcelain Enameled Faced Panels
07 21 00 - Thermal Insulation	07 44 53 - Glass-Fiber-Reinforced Cementitious Panels
07 22 00 - Roof and Deck Insulation	07 46 00 - Siding
07 24 00 - Exterior Insulation and Finish Systems	07 46 23 - Wood Siding
07 24 19 - Water-Drainage Exterior Insulation and Finish System	07 46 33 - Plastic Siding
07 25 00 - Water-Resistive Barriers/Weather Barriers	07 46 46 - Fiber-Cement Siding
07 27 00 - Air Barriers	07 52 00 - Modified Bituminous Sheet Roofing
07 30 05 - Roofing Felt and Underlayment	07 53 23 - Ethylene-Propylene-Diene-Monomer Roofing
07 31 00 - Shingles and Shakes	07 54 00 - Thermoplastic Membrane Roofing
07 31 13 - Asphalt Shingles	07 54 19 - Polyvinyl-Chloride Roofing
07 31 16 - Metal Shingles	07 54 23 - Thermoplastic-Polyolefin Roofing
07 31 29 - Wood Shingles and Shakes	07 56 00 - Fluid-Applied Roofing
07 31 33 - Composite Rubber Shakes	07 57 00 - Coated Foam Roofing
07 31 53 - Plastic Shakes	07 65 00 - Flexible Flashing
07 32 00 - Roof Tiles	07 71 16 - Manufactured Counterflashing Systems
07 32 01 - Roof Tile Accessories	07 72 26 - Ridge Vents
07 32 03 - Roof Tile Adhesive	07 72 27 - Eave Vents
07 32 13 - Clay Roof Tiles	07 72 29 - Roof Exhaust Vents
07 32 16 - Concrete Roof Tiles	07 77 00 - Wall Specialties
07 32 19 - Metal Roof Tiles	07 81 00 - Applied Fireproofing
07 32 26 - Plastic Roof Tiles	07 81 33 - Mineral-Fiber Fireproofing
07 40 00 - Roofing and Siding Panels	07 84 00 - Firestopping
07 41 00 – Roof Panels	07 84 16 - Annular Space Protection
07 41 13 - Metal Roof Panels	07 87 00 - Smoke Containment Barriers
07 41 43 - Composite Roof Panels	



07 21 00 - Thermal Insulation

6 Acceptance Criteria

AC02 Reflective Insulation AC12 Foam Plastic AC81 Cotton Fiber Insulation AC187 Polyester Loose-fill & Blanket Insulations AC220 Sheet Radiant Barriers

AC377 Spray Applied Foam Plastic Insulation

106 Evaluation Reports

5 VAR Environmental Reports

14 Listing Reports



Report Code References



QUPOND:

Example: Compliance to a direct reference

R703.2 Water-resistive barrier. One layer of No. 15 asphalt felt, free from holes and breaks, **Specific material** complying with ASTM D226 for Type 1 felt or other approved water-resistive barrier shall be applied over studs or sheathing of all exterior walls. Such felt or material shall be applied horizontally, with the upper layer lapped over the lower layer not less than 2 inches (51 **Specific installation** mm). Where joints occur, felt shall be lapped method not less than 6 inches (152 mm). The felt or other approved material shall be continuous to the top of walls and terminated at penetrations and building appendages in a manner to meet the requirements of the exterior wall envelope as described in Section R703.1.



Water-Resistive Barriers





L

	Material		Installation
Prescriptive Requirement	#15 Felt (ASTM D226 Type I)		Horizontally Lapped
Alternate Materials	Grade D Building Paper	AC38	Horizontally Lapped as Prescribed in Code
	Housewraps	AC38	Horizontally Lapped as Prescribed in Code
	Foam Plastic Sheathing Panels	AC71	Joint Treatment tested per AC71
	Trowel-, Spray-, or Roller- Applied Water Resistive Coatings over Exterior Cementitious Wall Coverings	AC209	Resistance to Joint Movement tested per AC209
	Water-Resistive Coatings over Exterior Sheathing	AC212	Resistance to Joint Movement tested per AC209
	Water Resistive Membrandes Factory –Bonded to Wood- Based Structural Sheathing	AC310	Joint Treatment tested per AC310
	Laminated Fibrous Board Sheathing	AC382	Joint Treatment tested per AC382



	~		
ES ICC EVALUATION SERVICE	Most Widely Accepted and Trusted		
ICC-ES Evaluation Report	ESR-2375 Relssued October 2015		
www.icc-es.org (800) 423-6587 (562) 699-054	A Subsidiary of the International Code Council®		Applicable codes
DIVISION: 07 00 00—THERMAL AND MOISTURE PROTECTION Soldin: 07 26 00—Water-Recistive Barriers/Weather	1.2 Evaluation to the following green codes and/or standards:		7
Barriers Section: 07 27 00—Air Barriers	(CALGreen), Title 24, Part 11 2012 and 2015 International Green Construction Code [®]		
REPORT HOLDER:	(IgCC) 2011 and 2014 ANSI/ASHRAE/USGBC/IES Standard 159.1-Standard for the Design of High-Performance	1.1 (Compliance with the following codes:
JUPONT BUILDING INNOVATIONS CHESTNUT RUN PLAZA POST OFFICE BOX 80721	Green Buildings, Except Low-Rise Residential Building 2012 and 2008 ICC 700 National Green	■ 20 ⁻	15, 2012 and 2009 <i>International Building Code</i> [⊮] (IBC)
WILMINGTON, DELAWARE 18880-0721 (800) 44-TYVEK www.construction.tvvek.com	standard ** (ICC 700-2012 and ICC 700-2004 2.0 USES	■ 20 ⁴	15, 2012 and 2009 <i>International Residential Code</i> ®
tyvekinf@usa.dupont.com	DuPont™ Tyvek [®] HomeWrap [®] -Sk DuPont™ Tyvek [®] StuccoWrap [®] -Style 10 Dit™ Tyvek [®] Droin/Wrap [™] -Style 1020 Dont™ Tyvek [®]		
DUPONT™ TYVEK [®] HOMEWRAP [®] -§TYLE 1066B; DUPONT™ TYVEK [®] STUCCOWRAP [®] -STYLE 1062X; DUPONT™ TYVEK [®] DRAINWRAP [™] -STYLE 1083X; DUPONT™ TYVEK [®] COMMERCIALWRAP [®] -STYLE 1182B; DUPONT™ TYVEK [®] COMMERCIALWRAP [®] D-STYLE 1083; AND DUPONT™ TYVEK [®] HEADERWRAP [®]	CommercialWap -Style Difference of the Style	■ 20 ⁻ Co ■ Oth	15, 2012 and 2009 <i>International Energy Conservation de[®] (IECC)</i> her Codes (see Section 8.0)
1.0 EVALUATION SCOPE 1.1 Compliance with the following order:	Section 2510.6 and IRC Section R703.6.3. All products may be used as all barrier materials under IRC Section N102.4.1 and IECC Sections 402.4 and 502.4.		1.2 Evaluation to the following green codes and/ standards:
 2015, 2012 and 2009 International Building Code[®] (IBC) 2015, 2012 and 2009 International Residential Code[®] (IRC) 	DuPont™ Tyvek DrainWrap™-Otyle 1062X, DuPont™ Tyvek DrainWrap™-Otyle 1063X and DuPont™ Tyvek CommercialWrap D-Style 1063 may be		■ 2013 California Green Building Standards Co
 2015, 2012 and 2009 International Energy Conservation Code[®] (IECC) 	8.0 OTHER CODES		(CALGreen), Title 24, Part 11
Other Codes (see Section 8.0) Properties evaluated:	8.1 Evaluation Scope:		2012 and 2015 International Green Construction Code (IgCC)
Water resistance Surface-burning characteristics Air leakage	In addition to the codes referenced in products covered in this report wer compliance with the requirements of the f	Section re evalu following (2011 and 2014 ANSI/ASHRAE/USGBC/IES Standa 2021 Standard for the Design of Uinh Defension
■ Wall draining characteristics (DuPont™ Tyvek StuccoWrap [®] -Style 1052X, DuPont™ Tyvek DrainWrap [®] -Style 1053X and DuPont™ Tyvek	■ 2006 International Building Code [®] (200	06 IBC)	Green Buildings, Except Low-Rise Residential Building
CommercialWrap* D-Style 1083 only) for EIFS and one coat stucco Exterior walls of Types I, II, III and IV construction	■ 2006 International Residential Code [®] (2006 IRC	■ 2012 and 2008 ICC 700 National Green Buildi
(DuPont™ Tyvet [®] CommercialWrap [®] -Btyle 1162E DuPont™ Tyvet [®] CommercialWrap [®] D-Btyle 1083 only	 2006 International Energy Conservat IECC) 	tion Code	Standard™ (ICC 700-2012 and ICC 700-2008)
CC 45: Budieston Reports are not to be construed as representing seathering in any at an audionomous of the outputs of the report or a recommendation for its use. There is any fluiding or other matter in this report, or as to any product sorrered by the repo	■ 2003 International Building Code [®] (200	03 IBC)	
Copyright © 2015 ICC Evaluation Service, LLC, All rights reserved.	 2003 International Residential Code[®] (2003 IRC)	
	 2003 International Energy Conserval IECC) 	tion Code [®]	^b (2003

ES ICC EVALUATION SERVICE	Most Widely Accept	pted and Trusted
ICC-ES Evaluation Report	l Reissued This report is subject to renewal (ESR-2375 # October 2015 # October 2017.
www.lcc-es.org (800) 423-6587 (562) 699-0543	A Subsidiary of the International C	Code Council®
DIVISION: 07 00 00—THERMAL AND MOISTURE PROTECTION Section: 07 25 00—Water-Resistive Barriers/Weather	1.2 Evaluation to the following gree standards: 2013 California Green Building (en oodec and/or Standards Code
Barriers Section: 07 27 00—Air Barriers	(CALGreen), Title 24, Part 11 2012 and 2015 International Green Co	Construction Code*
REPORT HOLDER:		
E.I. DUPONT DE NEMOURS & COMPANY, INC. (DUPONT™) DUPONT BUILDING INNOVATIONS CHESTNUT RUN PLAZA	189.1-Standard for the Design of H Green Buildings, Except Low-Rise Res	High-Performance Isidential Buildings
POST OFFICE BOX 80721 WILMINGTON, DELAWARE 18880-0721	■ 2012 and 2008 ICC 700 National Standard™ (ICC 700-2012 and ICC 70	J Green Building 00-2008)
www.construction.tvvek.com	2.0 USE8	
svekinggues.cupont.som	DuPont™ Tyvek" HomeWrap"-Style 1 Tyvek® StuccoWrap®-Style 1062X; D	1055B; DuPon DuPont ^a
EVALUATION SUBJECT:	DrainWrap™-Style 1063X; DuP	Pont**
DUPONT™ TYVEK [®] HOMEWRAP [®] -8TYLE 1066B; DUPONT™ TYVEK [®] STUCCOWRAP [®] -8TYLE 1082X; DUPONT™ TYVEK [®] BAINWRAP [™] -8TYLE 1083X; DUPONT™ TYVEK [®] COMMERCIALWRAP [®] -8TYLE 1182B; DUPONT™ TYVEK [®] COMMERCIALWRAP [®] D-8TYLE 1083; AND DUPONT™ TYVEK [®] HEADERWRAP [®]	Commercial/Wrap [®] D-Style 1083; and Header/Wrap [®] are used as water-re- exterior side of exterior construction type under the under the IRC, except as equivalent to Grade as resistance rating	operties evaluated:
1.0 EVALUATION SCOPE	Section 2510.6 may be use arrie	Water resistance
1.1 Compliance with the following oddec:	N1102.4 oC Secto	
2015, 2012 and 2009 International Building Code [®] (IBC)	In DuPont ^{ex} Tyy	Surface-burning characteristics
 2015, 2012 and 2009 International Residential Code[®] (IRC) 	ont™ Tyvek® Commen used as components of	Surface-burning characteristics
 2015, 2012 and 2009 International Energy Conser Code[®] (IECC) 	s.0 DESCRIPTION	Air leakage
Other Codes (see Section 8.0)	3.1 General:	
Properties evaluated:	The products described in	Wall draining characteristics (DuPont™ Tyyek [®]
Water resistance	that are manufactured for	
Surface-burning characteristics	fibers combined with an	StuccoWrap [™] -Style 1062X. DuPont [™] Tyvek [™]
Air leakage	The products have been	Design March 10022 and DuDagt M. Taus 10
 Wall draining characteristics (DuPont[™] Tyvek[®] StuccoWrap[®]=Style 1052X, DuPont[™] Tyvek[®] DrainWrap[™]=Style 1053X and DuPont[™] Tyvek[®] CommercialWrap[®] D-Obyle 1083 only) for EIF6 and one- coat stucco 	into sneets with variations through 3.5. All products have a flams and a smoke-developed i tested in accordance of AS'	CommercialWrap [®] D-Style 1083 only) for EIFS and one-
 Exterior walls of Types I, II, III and IV construction (DuPont¹⁴ Types[®] CommercialWrap[®]-Btyle 1162B; DuPont¹⁸ Types[®] CommercialWrap[®]-Btyle 1162B; 	The sheet materials ha exceeding 0.02 L/s-m ² (0.0 when used as an air barrier	coal slucto
Duront - Tyvek CommercialWitap Droghe tuda only)		Exterior walls of Types I, II, III and IV construction
EC-AS Includents Reports are not to be constrained as representing auxiliaries or any other as an endotroimment of the endpact of the report or a recommendation for m use. There is no to any fidding or other matter in this report, or as its any product contend by the report.	e attributes not spacefloadly addressed, nor a o warrange by ICC Realisation Services, ILC,	(DuPont [™] Tyvek [®] CommercialWrap [®] –Style 1162B;
copyrgm or 2015 FCC Evaluation Service, LLC. All rights reserved.		DuPont™ Tyvek CommercialWrap D-Style 1083 only)

D





Most Widely Accepted and Trusted

ESR-2375

ICC-ES Evaluation Report

Reissued October 2015 This report is subject to renewal October 2017.

www.lcc-es.org | (800) 423-6587 | (562) 699-0543 A Subsidiary of the International Code Council®

DIVISION: 07 00 00-THERMAL AND MOISTURE PROTECTION Section: 07 25 00-Water-Reciptive Barriers/Weather

Barriers Section: 07 27 00—Air Barriers

REPORT HOLDER:

EL DUPONT DE NEMOURS & COMPANY, INC. (DUPONT[™]) DUPONT BUILDING INNOVATIONS CHESTNUT RUN PLAZA POST OFFICE BOX 80721 WILMINGTON, DELAWARE 18880-0721 (800) 44-TYVEX www.construction.tvvek.com tyvekinf@usa.dupont.com

EVALUATION SUBJECT:

DUPONT[™] TYVEK[®] HOMEWRAP[®]-STYLE 1066B; DUPONT[™] TYVEK[®] STUCCOWRAP[®]-STYLE 1062X; DUPONT[™] TYVEK[®] COMMERCIALWRAP[®]-STYLE 1083; DUPONT[™] TYVEK[®] COMMERCIALWRAP[®] D-STYLE 1083; AND DUPONT[™] TYVEK[®] HEADERWRAP[®]

1.0 EVALUATION SCOPE

1.1 Compliance with the following oddes:

- 2015, 2012 and 2009 International Building Code[®] (IBC)
 2015, 2012 and 2009 International Residential Code[®]
- (IRC)
- 2015, 2012 and 2009 International Energy Conservation Code[®] (IECC)
- Other Codes (see Section 8.0)
- Properties evaluated:
- Water resistance
- Surface-burning characteristics
- Air leakage
- Wall draining characteristics (DuPont[™] Tyvek[®] StuccoWrap[™]-Style 1052X, DuPont[™] Tyvek[®] DrainWrap[™]-Style 1053X and DuPont[™] Tyvek[®] CommerciaWrap[®] D-Style 1083 only) for EIF8 and one-coat stucco
- Exterior waits of Types I, II, III and IV construction (DuPont™ Tyvex[®] CommercialWrap[®]-Btyle 1162B; DuPont™ Tyvex[®] CommercialWrap[®] D-Btyle 1083 only)

1.2 Evaluation to the following green codec and/or standards:

- 2013 California Green Building Standards Code (CALGreen), Title 24, Part 11
- 2012 and 2015 International Green Construction Code[®] (IgCC)
- 2011 and 2014 ANSI/ASHRAE/USGBC/IES Standard 189.1–Standard for the Design of High-Performance Green Buildings, Except Low-Rise Residential Buildings
- 2012 and 2008 ICC 700 National Green Building Standard ^M (ICC 700-2012 and ICC 700-2008)

2.0 USES

DuPont™ Tyvek[®] HomeWrap[®]-Style 10558; DuPont™ Tyvek[®] StuccoWrap[®]-Style 1052X; DuPont™ Tyvek[®] DrainWrap[®]-Style 1053X; DuPont™ Tyvek[®] CommercialWrap[®] D-Style 1053; and DuPont™ Tyvek[®] HeaderWrap[®] are used as water-resistive barriers on the exterior side of exterior walls of buildings of any construction type under the IBC and construction permitted under the IRC, except as noted in Section 4.5. They are equivalent to Grade D paper with a 60-minute water resistance rating as described in 2012 and 2009 Section 2510.6 and IRC Section R703.6.3. All per may be used as air barrier materials under IRC N1102.4.1 and IECC Sections 702.4 and 502.4.

in addition, DuPont™ Tyvek[®] StuccoWrap[®]-DuPont™ Tyvek[®] Drain/Wrap[®]-Btyle DuPont™ Tyvek[®] Commercial/Wrap[®] D-St used as components of an EIFS of e-coat stucco drainage system as described in Sect. 4.4.

3.0 DESCRIPTION

3.1 General:

The products described in this report are comprised of nonworen, fash spunbonded, nonperforated, olefin sheets that are manufactured from high-density polyethylene fibers combined with an ultraviolet stabilizing additive. The products have been bonded by heat and pressure into sheets with variations as described in Sections 3.2 through 3.6.

All products have a fame spread index of less than 25 and a smoke-developed index of less than 450, when tested in accordance of ASTM E84.

The sheet materials have an air leakage rate not exceeding 0.02 L/s-m² (0.004 cfm/ft² at 0.3 w.g. (1.57 psf)) when used as an air barrier material.

(ANS)

Page 1 of 6

N IN

ECOS Biolization Reports are not to be construed as representing antilents in any other attributes not specifically addressed, nor are they to be construed at an addressman af the industry of the report or a traceonouslation for its use. There is no varianty by ICC Reduction Section, ILC, appears or implied, a trace fidding or other matter in the report, or as its and product scored by the report.

Copyright © 2015 ICC Evaluation Service, LLC. All rights reserved.

Descriptive Information

QU POND.

E8R-2376 | Most Widely Accepted and Trusted

The attributes of the water-resistive barriers have been verified as conforming to the requirements of (I) 2013 CALGreen Section A4.07.5 for air barriers; (II) 2012 and 2015 [gcC Section 605.1.2.1 for air barriers; (II) 2012 and 2015 [gcC Section 605.1.2.1 and 2011 A3HRAE 189.1 Section 7.3.1.1 and 2011 A3HRAE 189.1 Section 7.4.2.9 for air barriers; (IV) ICC 700-2012 Section 502.1.8 and ICC 700-2008 Section 502.2.9 for water-resistive barriers. Note that decisions on compliance for those areas rest with the user of this report. The user is advised of the project-specific provisions that may be contingent upon meeting specific conditions, and the verification of those conditions is outside the scope of this report. These codes or standards often provide supplemental information as outside.

3.2 DuPont™ Tyvek® HomeWrap®-Style 10668:

This product is a smooth sheet with a nominal basis weight of 1.8 ounces per square yard (51 grams per square meter) and is produced in rolls of varying sizes.

3.3 DuPont[™] Tyvek[®] StucooWrap[®]-Style 1062X:

The product has a surface texture that is intended to allow for drainage of water that may get behind the exterior wall finish material. This product has a nominal basis weight of 2.1 ounces per square yard (71 grams per square meter) and is produced in nois of varying sizes.

3.4 DuPont™ Tyvek® DrainWrap™-Style 1063X:

The product has a surface texture that is intended to allow for drainage of water that may get behind the exterior wall finish material. This product has a nominal basis weight of 2.1 ounces per square yard (71 grams per square meter) and is produced in rolls of varying sizes.

3.6 DuPont[™] Tyvek[®] CommercialWrap[®]-Style 1162B:

This product is a smooth sheet with a nominal basis weight of 2.7 ounces per square yard (92 grams per square meter) and is produced in rols of varying sizes.

3.6 DuPont™ Tyvek[®] HeaderWrap[®]:

This product is the same as Tyvek[®] HomeWrap[®]-Style 1055B, except that the rolls are narrower.

8.7 DuPont™ Tyvek® CommercialWrap® D-Style 1083:

The product has a surface texture that is intended to allow for drainage of water that may get behind the exterior wall finish material. This product has a nominal basis weight of 2.4 ounces per square yard (81 grams per square meter) and is produced in rolls of varying sizes.

4.0 INSTALLATION

4.1 General:

The manufacturer's published installation instructions and this report must be strictly adhered to. If requested by the code official, a copy of this report must be available at the jobsite during installation.

The use of Tyvek[®] HeaderWirap[®] in conjunction with any of the products recognized in Sections 3.2 through 3.5 is optional. The use of tage to seal seams and edges of the products is optional, except as described in Section 4.3 and where required by the manufacturer's installation instructions.

4.2 Water-reciptive Barrier.

The water-resistive barriers described in this report are installed after wall framing is completed. The roll is placed 6 to 12 inches (152 to 305 mm) from the starting corner and fastened to the sheathing with corrosion-resistant staples or nails approved by the manufacturer, and is then unrolled around the building and fastened as set forth in the manufacturer's published installation instructions at top and bottom still plates and at framing members. A minimum of 6 inches (152 mm) of overlap is provided for vertical seams and 2 inches (51 mm) for horizontal seams, except where the manufacturer's installation instructions specify a greater overlap dimension. When use is over wood-based sheathing in exterior plaster applications, two layers of a water-resistive barrier must be applied over sheathing in accordance with IBC Section 2510.5 or IRC Section R703.6.3. For cementitious coatings or exterior insulation and finish systems, application must be in accordance with the evaluation report on the exterior coating.

Page 2 of 8

4.3 Air Barrier Material:

When used as an air barrier material or as a component of an air barrier assembly, the products must be installed in accordance with the manufacturer's published installation instructions and this report.

4.4 Wall Covering Assembly with Drainage:

The assembly described in this section complies with Section 4.5 of the ICC-ES Acceptance Oriteria for EIFS Clad Drainage Wall Assemblies (AC235) and Section 3.2.10 of the ICC-ES Acceptance Criteria for Cementitious Exterior Wall Coatings (AC11). The assembly is limited to Type V construction, and may be used in Group R, Division 1 and 3. Occupancies. The system consists of minimum (116-inch-thick (11.1 mm) Exterior or Exposure plywood or Exposure 1 oriented strand board ap to wood studs spaced a maximum of 16 inches (42 on center and fastened in accordance requirements of Chapter 23 of the IBC or the IRC. Vertical board edges must b DuPont™ Twek® StuccoWrap®-Style Tyvek[®] DrainWrap[™]-Style 1063X Commercia/Wrap[®] D-Style 1082 Tyvek[®] applied as described in Section 4.2. For 1-inch-th/ck (25.4 mm) flat or grocy one I expanded polystyrene (EPS) foars ards, recognized in a current ICC-ES evaluate as complying with ASTM yvek* StuccoWrap*, Tyvek* C 578, are placed. mmercialWrap® D and fastened DrainWrap[™] or ong the EPS edges and midway to the sheat contail edges. The fastener spacing must between th not exc Inches (610 mm) on center along the EPS edge midway locations, the fastener spacing must ceed 16 inches (406 mm) on center and fasteners st be located within 16 inches (406 mm) of the horizontal edges. Fasteners consist of wood screws sized to meet wind resistance requirements, with minimum 17/4-inch-diameter (45 mm) plates or washers, and penetrating a minimum of 1/4 inch (6.4 mm) through the sheathing Weep screeds, as set forth in IBC Section 2512.1.2 or IRC Section R703.6.2.1, must be installed. The EIFS base coat, fabric and finish coat must be installed over the EPS in accordance with the EIFS manufacturer's ICC-ES evaluation report. The one-coat stucco system must be installed in accordance with the manufacturer's ICC-ES evaluation report.

4.6 Exterior Walls of Types I, II III and IV Construction:

4.6.1 DuPont™ Tyvek® HomeWrap®-Style 10558; DuPont™ Tyvek® StuccoWrap®-Style 1052X; DuPont™ Tyvek® DrainWrap®-Style 1053X; DuPont™ Tyvek® HeaderWrap® may be used on exterior walls of Types I, II, III or IV construction 40 feet or less above grade plane. The use Is not limited to any specific assembly, except where the wall assembly uses foam plastic insulation it must also comply with the requirements of IBC Section 2603.5.

Installation

Specific to end-use:

- Water-Resistive Barrier
- Air Barrier
- Wall Covering Assembly with D rainage
- Exterior Walls or Types I, II, III and IV Construction



ESR-2376 | Most Widely Accepted and Trusted

4.6.2 The DuPont™ Tyvek[®] CommercialWrap[®]-Style 1162B and DuPont™ Tyvek[®] CommercialWrap[®] D-Style 1083 may be used as a component of exterior walls of buildings of Type I, II, II or IV construction as follows:

Under the 2016 and 2012 IBC: Use on exterior walls greater than 40 feet in height above grade is limited to the assemblies described in Table 1. The use on exterior walls of Types I, II, III or IV construction 40 feet or less above grade plane is not limited to any specific assembly, except that wall assemblies that use foam plastic insulation must also comply with the requirements of IBC Section 2603.5.

Under the 2008 and 2008 IBC: Use on exterior wails greater than 40 feet in height above grade is not limited to any specific assembly, except that wall assemblies that use foam plastic insulation must also comply with the requirements of IBC Gection 2603.5.

6.0 CONDITIONS OF USE

The DuPont™ Tyvek[®] products described in this report comply with, or are suitable alternatives to what is specified in, those codes listed in Section 1.0 of this report, subject to the following conditions:

- 5.1 The products must be installed in accordance with the manufacturer's published installation instructions, the requirements of the applicable code and this report. In the event of a conflict between this report and the manufacturer's published installation instructions, this report governs.
- 6.2 The water-resistive barriers must be covered by an exterior wall finish complying with the requirements of the applicable code.
- 5.3 When DuPont[™] Tyvek[®] StuccoWrap[®]-Style 1062X, DuPont[™] Tyvek[®] DrainWrap[™]-Style 1063X or Dupont[™] Tyvek[®] CommercialWrap[®] D-Style 1083 are used in an EIFS wall covering assembly with drainage or a one-coat stucco assembly as described in Section 4.4, the assembly must be specifically recognized in the evaluation report on the EIFS or one-coat stucco.
- 5.4 This report provides air leakage rates for the products as an air barrier material only. When used as a component of an air barrier assembly, the design and evaluation of the air barrier assembly of which they are a component must be provided to the satisfaction of the code official.
- 6.6 Use of DuPont™ Tyvek[®] CommercialWrap[®]-Gtyle 1162B and DuPont™ Tyvek[®] CommercialWrap[®] D-Style 1083 on exterior wails of buildings of Type I, II, III or IV construction must be in accordance with the requirements of Section 4.5 for the applicable edition of the code.

8.0 EVIDENCE SUBMITTED

 Data in accordance with the ICC-E3 Acceptance Criteria for Water-resistive Barriers (AC38), dated January 2015.

Page 3 of 6

- Bata in accordance with Section 4.10 of the ICC-ES Acceptance Criteria for EIFS Clad Drainage Wall Assemblies (AC235), dated January 2015.
- 6.3 Report of testing in accordance with ASTM E84.
- 8.4 Reports of testing in accordance with ASTM E2178.
- Reports of testing in accordance with NFPA 285 with related engineering analysis.

7.0 IDENTIFICATION

The products described in this report are identified by a label on the container of each roll of membrane, and by printing on the product that includes the report holder's name, address, and telephone number; the product name and the evaluation report number (Son

8.0 OTHER CODE 8.1 Evaluation Scope:

In addition to the codes referenced in Section 1.0, the products covered in this report were evaluated for compliance with the requirements of the following codes:

- 2006 International Building Code[®] (2006 IBC)
- 2005 International Residential Code[®] (2005 IRC)
 2005 International Energy Conservation Code[®] (2005 IECC)
- 2003 International Building Code[®] (2003 IBC)
- 2003 International Residential Code[®] (2003 IRC)
- 2003 International Energy Conservation Code[®] (2003 IECC)
- 8.2 Uses
- See Section 2.0.
- 8.3 Decoription
- See Section 3.0.
- 8.4 Installation
- See Section 4.0.
- 8.6 Conditions of Use
- See Section 5.0.
- 8.8 Evidence Submitted
- See Section 6.0.
- 8.7 Identification See Section 7.0.

Conditions for Use

5.0 CONDITIONS OF USE

The DuPont[™] Tyvek[®] products described in this report comply with, or are suitable alternatives to what is specified in, those codes listed in Section 1.0 of this report, subject to the following conditions:

- 5.1 The products must be installed in accordance with the manufacturer's published installation instructions, the requirements of the applicable code and this report. In the event of a conflict between this report and the manufacturer's published installation instructions, this report governs.
- 5.2 The water-resistive barriers must be covered by an exterior wall finish complying with the requirements of the applicable code.
- 5.3 When DuPont[™] Tyvek[®] StuccoWrap[®]-Style 1062X, DuPont[™] Tyvek[®] DrainWrap[™]-Style 1063X or Dupont[™] Tyvek[®] CommercialWrap[®] D-Style 1083 are used in an EIFS wall covering assembly with drainage or a one-coat stucco assembly as described in Section 4.4, the assembly must be specifically recognized in the evaluation report on the EIFS or one-coat stucco.
- 5.4 This report provides air leakage rates for the products as an air barrier material only. When used as a component of an air barrier assembly, the design and evaluation of the air barrier assembly of which they are a component must be provided to the satisfaction of the code official.
- 5.5 Use of DuPont[™] Tyvek[®] CommercialWrap[®]-Style 1162B and DuPont[™] Tyvek[®] CommercialWrap[®] D-Style 1083 on exterior walls of buildings of Type I, II, III or IV construction must be in accordance with the requirements of Section 4.5 for the applicable edition of the code.



ESR-2376 | Most Widely Accepted and Trusted

4.6.2 The DuPont[™] Tyvek[®] CommercialWrap[®]-Style 1162B and DuPont[™] Tyvek[®] CommercialWrap[®] D-Style 1083 may be used as a component of exterior walls of buildings of Type I, II, III or IV construction as follows:

Under the 2016 and 2012 IBC: Use on exterior walls greater than 40 feet in height above grade is limited to the assemblies described in Table 1. The use on exterior walls of Types I, II, III or IV construction 40 feet or less above grade plane is not limited to any specific assembly, except that wall assemblies that use foam plastic insulation must also comply with the requirements of IBC Section 2603.5.

Under the 2008 and 2008 IBC: Use on exterior wails greater than 40 feet in height above grade is not limited to any specific assembly, except that wall assemblies that use foam plastic insulation must also comply with the requirements of IBC Gection 2603.5.

6.0 CONDITIONS OF USE

The DuPont™ Tyvek[®] products described in this report comply with, or are suitable alternatives to what is specified in, those codes listed in Section 1.0 of this report, subject to the following conditions:

- 5.1 The products must be installed in accordance with the manufacturer's published installation instructions, the requirements of the applicable code and this report. In the event of a conflict between this report and the manufacturer's published installation instructions, this report governs.
- 6.2 The water-resistive barriers must be covered by an exterior wall finish complying with the requirements of the applicable code.
- 5.3 When DuPont[™] Tyvek[®] StuccoWrap[®]-Style 1062X, DuPont[™] Tyvek[®] DrainWrap[™]-Style 1063X or Dupont[™] Tyvek[®] CommercialWrap[®] D-Style 1083 are used in an EIFS wall covering assembly with drainage or a one-coat stucco assembly as described in Section 4.4, the assembly must be specifically recognized in the evaluation report on the EIFS or one-coat stucco.
- 5.4 This report provides air leakage rates for the products as an air barrier material only. When used as a component of an air barrier assembly, the design and evaluation of the air barrier assembly of which they are a component must be provided to the satisfaction of the code official.
- 5.6 Use of DuPont™ Tyvek[®] CommercialWrap[®]-Otyle A Id 11628 and DuPont™ Tyvek[®] CommercialWrap[®] D-Style 1083 on exterior wails of buildings of Type I, III or IV construction must be in accordance with requirements of Section 4.5 for the applicable dution of the code.
- **8.0 EVIDENCE SUBMITTED**
- Data in accordance with the ICC-ES Acceptance Criteria for Water-resistive Barriers (AC38), dated January 2015.

Page 3 of 6

- Bata in accordance with Section 4.10 of the ICC-ES Acceptance Criteria for EIFS Clad Drainage Wall Assemblies (AC235), dated January 2015.
- 6.3 Report of testing in accordance with ASTM E84.
- 8.4 Reports of testing in accordance with ASTM E2178.
- Reports of testing in accordance with NFPA 285 with related engineering analysis.

7.0 IDENTIFICATION

The products described in this report are identified by a label on the container of each roll of membrane, and by printing on the product that includes the report holder's name, address, and belephone number, the product name; and the evaluation report number (ESR-2375).

8.0 OTHER CODES 8.1 Evaluation Scope:

In addition to the codes referenced in Section 1.0, the products covered in this report were evaluated for compliance with the requirements of the following codes:

- 2006 International Building Code[®] (2006 IBC)
- 2006 International Residential Code[®] (2006 IRC)
 2006 International Energy Conservation Code[®] (2006
- IECC)
 2003 International Building Code[®] (2
- 2003 International Residential Code
- 2003 International Energy Conserv IECC)

8.2 Uses See Section 2.0.

8.3 Decoription See Section 3.0.

8.4 Installation See Section 4.0.

8.6 Conditio

See Sect

3 ection 6.0. 7 Identification See Section 7.0.

Evidence Submitted

6.0 EVIDENCE SUBMITTED

- 6.1 Data in accordance with the ICC-ES Acceptance Criteria for Water-resistive Barriers (AC38), dated January 2015.
- 6.2 Data in accordance with Section 4.10 of the ICC-ES Acceptance Criteria for EIFS Clad Drainage Wall Assemblies (AC235), dated January 2015.
- 6.3 Report of testing in accordance with ASTM E84.
- 6.4 Reports of testing in accordance with ASTM E2178.
- 6.5 Reports of testing in accordance with NFPA 285 with related engineering analysis.







Example: Moving from Alternate to Code Specified





SECTION 1408 EXTERIOR INSULATION AND FINISH SYSTEMS (EIFS)

1408.1 General. The provisions of this section shall govern the materials, construction and quality of exterior insulation and finish systems (EIFS) for use as *exterior wall coverings* in addition to other applicable requirements of Chapters 7, 14, 16, 17 and 26.

1408.2 Performance characteristics. EIFS shall be constructed such that it meets the performance characteristics required in ASTM E 2568.

[BS] 1408.3 Structural design. The underlying structural framing and substrate shall be designed and constructed to resist loads as required by Chapter 16.

1408.4 Weather resistance. EIFS shall comply with Section 1403 and shall be designed and constructed to resist wind and rain in accordance with this section and the manufacturer's application instructions.

1408.4.1 EIFS with drainage. EIFS with drainage shall have an average minimum drainage efficiency of 90 percent when tested in accordance the requirements of ASTM E 2273 and is required on framed walls of Type V construction, Group R1, R2, R3 and R4 occupancies.

1408.4.1.1 Water-resistive barrier. For EIFS with drainage, the *water-resistive barrier* shall comply with Section 1404.2 or ASTM E 2570.

1408.5 Installation. Installation of the EIFS and EIFS with drainage shall be in accordance with the EIFS manufacturer's instructions.

1408.6 Special inspections. EIFS installations shall comply with the provisions of Sections 1704.2 and 1705.16.



Process Alternates





Test Methods Substitution Example: Commercial Air Barrier

C402.5 Air leakage—thermal envelope (Mandatory). The thermal envelope of buildings shall comply with Sections C402.5.1 through C402.5.8, or the building thermal envelope shall be tested in accordance with ASTM E 779 at a pressure differential of 0.3 inch water gauge (75 Pa) or an equivalent method approved by the code official and deemed to comply with the provisions of this section when the tested air leakage rate of the building thermal envelope is not greater than 0.40 cfm/ft2 (0.2 L/s \cdot m2).









Example: Above Code Programs

R102.1.1 Above code programs. The code official or other authority having jurisdiction shall be permitted to deem a national, state or local energy-efficiency program to exceed the energy efficiency required by this code. Buildings approved in writing by such an energy-efficiency program shall be considered in compliance with this code. The requirements identified as "mandatory" in Chapter 4 shall be met.



Summary



- Alternate materials and methods all ow for innovation
- Evaluation reports are an important resource to the code official
- □ Code official is the ultimate authority





Questions



Copyright© 2016 E. I. du Pont de Nemours and Company. The DuPont Oval, DuPont[™] and The miracles of science[™] are trademarks of E. I. du Pont de Nemours and Company or its affiliates. All rights reserved.



The miracles of science™